


AISI Air Grade T3 To T8 Polished 2024 Aluminum Flat Bar 0.3mm For Hardware Fields

Our Product Introduction

Basic Information

- Place of Origin: Jiangsu, China
- Brand Name: LIANZHONG
- Certification: ISO9001
- Model Number: 1000series, 2000series, 3000series, 5000series, 6000series, 7000series
- Minimum Order Quantity: 1 ton
- Price: Negotiable
- Packaging Details: Exporting package/wooden box package etc
- Delivery Time: 3-15 days
- Payment Terms: L/C, T/T, Western Union
- Supply Ability: 20000 Ton/Tons per Month



Product Specification

- Shape: Square
- Model Number: 6063
- Tolerance: $\pm 1\%$
- Length: 6m
- Color: Silver
- Delivery Time: 8-14 Days
- Highlight: **AISI polished aluminum flat bar, Air Grade 2024 aluminum flat bar, aluminum flat bar 0.3mm**



Product Description

AISI Air Grade T3 - T8 Mill Finish Polished 2024 Aluminium Flat Bar 0.30mm

How strong is aluminum flat bar?

Aluminum flat bar provides superior strength. This varies by grade, but 6061 aluminum, in particular, has a shear strength of 30 kilopounds per square inch, a yield point of 40 ksi, and a tensile strength of 45 ksi.


What are aluminum flat bars used for?

Flat bar is a basic of building support materials. They are generally used for support braces, ladder hangers, gate latches, duct work, overhead doors, heaters and bracing.

Temper	O, H12, H14, H16, H18, H22, H24, H26, H32, H112
Thickness	0.1mm - 260mm
Width	500-2000mm
Length	to clients' requirement
Coating	Polyester, Fluorocarbon, polyurethane and epoxy coating(PE/FC/PUR/EPOXY)
Surface	Mill finished, Coated, Embossed, Brushed, Polished, Mirror, Anodized, etc
Gloss	Meet the customer requirement
Material	Aluminum Flat Bar
Standard	GB/T3190-2008, GB/T3880-2006, ASTM B209, JIS H4000-2006, etc
OEM service	Perforated, Cutting special size, Doing flatness, Surface treatment, etc
Usage	Construction filed, Ships building industry, Decoration, Industry, Manufacture, Machinery and hardware fields, etc
Delivery	In general, within 7-15 working days after receiving deposit or According to Final order quantity
Packaging Details	Standard export package. One pallet is about 2-3 ton. Two steel belts in width and three in width. One 20GP container can load about 18-20 tons Aluminium Sheet. One 40GP container can load about 24 tons Aluminium Sheet

Grade	Hardness	Tensile Strength (MPa)	Yield Strength (MPa)	Elongation(%)	
				0.25-1.25mm	1.26-3.0mm
1100	O	89.6	34.5	30	6
	H12	110.3	103.4	4	12
	H14	124.1	117.2	3	10
2024	O	186.2	75.8	18	20
	T3	482.6	344.7	16	18
	T4	468.8	324.1	20	19
3003	O	110.3	41.4	30	33
	H12	131	124.1	9	11
	H14	151.7	144.8	3	7
5052	O	193.1	89.6	20	21
	H32	227.5	193.1	7	10
	H34	262	213.7	6	8
5083	O	275.8	144.8	21	25
	H32	282.7	151.7	20	21
	H34	330.9	255.1	11	14
6061	O	124.1	55.2	25	26
	T4	241.3	144.8	22	24
	T6	310.3	275.8	12	17
7075	O	227.5	103.4	16	18
	T6	572.3	503.3	11	12

Product Details





Packing and Shippment





Certification



JIANGSU LIANZHONG METAL PRODUCTS (GROUP) CO., LTD



+8618151700330



sales02@jslzsteel.com



aluminium-sheetcoil.com

Guang Yi Columbus B Tower, Wuxi, Jiangsu, China