

# ASTM 6000 Series Silver Aluminium H Beam Support 10mm Galvanized H Beam

# **Basic Information**

Place of Origin: Jiangsu,China
Brand Name: LIANZHONG
Certification: ISO9001

Model Number: 1000series, 2000series, 3000series, 3000series,

5000series, 6000series, 7000series

Minimum Order Quantity: 1ton

• Price: Negotiable

Packaging Details: Exporting package/wooden box package etc

Delivery Time: 3-15 days

Payment Terms: L/C, T/T, Western Union
Supply Ability: 20000 Ton/Tons per Month



# **Product Specification**

Shape: H ShapeWall Thickness: 0.8-10mm


• Length: Max 6.0m Or Customized

Color: SilverFinish: MillApplication: Industry

• Highlight: Aluminium H Beam 10mm,

6000 Series galvanized h beam,

h beam support 10mm



# ASTM 6000 Series Silver Aluminium H Beam 10mm Used For Industry

#### What are aluminum beams used for?

Typical applications include structural components for commercial sites and residential homes such as rafters, awnings, trailers, overhead supports and walkways. Aluminum Association beam products tend to be more versatile as the thicker, straight-edged flanges allow for easier connections and fitting.

#### Where is I-beam used?

What are H Beams used for? H Beams are commonly used in the construction of buildings as well but also large trailers and bridges, among others. Due to their slightly different cross-section shape, thicker central web and wider flanges, H beams can bear larger loads than I beams.

Product Name	H Beam					
Technique	Hot Rolled/Cold Rolled/Galvanized					
Length	1-12m or customer request					
Flange Width	Flange Width 50-400mm					
Flange Thickness	4.5-23mm					
Web Width	100-900mm					
Web Thickness	5-16mm					
Tolerance	土1%					
Processing Service	* IVVEIDING PUNCHING CHITING					
Packing	By bundles with steel strips or as customer request					
Delivery time In 10-25 days after receipt of deposit or L/C,T/T						

Grade	Hardne	Tensile Strength	Yield Strength	Elongation(%)	
	ss	(MPa)	(MPa)	0.25-1.25mm	1.26-3.0mm
1100	0	89.6	34.5	30	6
	H12	110.3	103.4	4	12
	H14	124.1	117.2	3	10
2024	0	186.2	75.8	18	20
	T3	482.6	344.7	16	18
	T4	468.8	324.1	20	19
3003	0	110.3	41.4	30	33
	H12	131	124.1	9	11
	H14	151.7	144.8	3	7
5052	0	193.1	89.6	20	21
	H32	227.5	193.1	7	10
	H34	262	213.7	6	8
5083	0	275.8	144.8	21	25
	H32	282.7	151.7	20	21
	H34	330.9	255.1	11	14
6061	0	124.1	55.2	25	26
	T4	241.3	144.8	22	24
	T6	310.3	275.8	12	17
7075	0	227.5	103.4	16	18
	T6	572.3	503.3	11	12

### **Product Details**



**Packing and Shippment** 



# Certification



# JIANGSU LIANZHONG METAL PRODUCTS (GROUP) CO., LTD



+8618151700330



sales02@jslzsteel.com aluminium-sheetcoil.com



Guang Yi Columbus B Tower, Wuxi, Jiangsu, China