

# ASTM 3003 Polished Aluminum Pipe 0.3mm

#### **Basic Information**

Place of Origin: Jiangsu,China
 Brand Name: LIANZHONG
 Certification: ISO9001

Model Number: 1000series, 2000series, 3000series, 3000series,

5000series, 6000series, 7000series

Minimum Order Quantity: 1ton

• Price: Negotiable

Packaging Details: Exporting package/wooden box package/Or

per customers'requirement

• Delivery Time: 3-15 days

Payment Terms: L/C, T/T, Western Union
 Supply Ability: 20000 Ton/Tons per Month



## **Product Specification**

Grade: 3000 Series
Hardness: 160-205 Rm/Mpa
Wall Thickness: 0.3mm-50mm

Model Number: 3003MOQ: 3 TonsAlloy Or Not: Is Alloy

• Highlight: polished aluminum pipe 0.3mm,

Polished 3003 aluminum pipe,

3003 aluminum tube



#### ASTM 3003 Polished Surface Aluminum Pipe 0.3mm For Storage Device

3003 is AL-Mn alloy, which is the most widely used antirust aluminum. The strength of this alloy is not high (slightly higher than that of industrial pure aluminum), and it cannot be strengthened by heat treatment. Therefore, cold working method is adopted to improve its mechanical properties: In the annealing state has a high plasticity, in the semi-cold hardening plasticity is good, cold hardening plasticity is low, good corrosion resistance, good weldability, bad machinability.

3003 aluminum tube has good formability, solubility and corrosion resistance. It is used for processing parts that need to have good formability, high corrosion resistance and good weldability, or require both these properties and high strength than 1XXX series alloy.

Application range:

such as kitchenware, food and chemical products processing and storage equipment, liquid product transport tank, tank, all kinds of pressure vessels and pipelines processed by thin plate general utensils, heat sink, makeup plate, photocopier drum, ship materials.

Place of Origin	China
Grade	3000 Series
Shape	Round
Surface Treatment	Polished
Length	customized
Usage	industry, decoration
Hardness	160-205 Rm/Mpa
Alloy Or Not	Is Alloy
Temper	T3 - T8
Al (Min)	98.8%
Wall Thickness	0.3mm-50mm
Tolerance	±1%
Processing	Bending, Decoiling, Welding, Punching,
Service	Cutting
Surface	mill finish, anodized, polished etc
Surface Color	silver, bronze, champagne etc.
Processing	extrusion, drawn, rolled etc
Certificate	ISO, CE etc
MOQ	3 Tons
Payment term	L/C T/T/Western Union

#### **Product Details**





### Certification



# JIANGSU LIANZHONG METAL PRODUCTS (GROUP) CO., LTD





Guang Yi Columbus B Tower, Wuxi, Jiangsu, China