

# Decorations Aluminium H Section 0.3mm Thick 6061 T6 Galvanized H Channel

### **Basic Information**

- Place of Origin:
- Brand Name:
- Certification: ISO9001
- Model Number:
- Minimum Order Quantity: 1ton
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T, Western Union
- Supply Ability: 20000 Ton/Tons per Month



## **Product Specification**

- Wall Thickness:
- Temper:
- Delivery Time:
- Length:
- Tolerance:
- Application:
- Highlight:
- 0.4-100mm Or Accept The Customization T3-T8 15-21 Days

1000series, 2000series, 3000series,

5000series, 6000series, 7000series

Exporting package/wooden box package etc

Custom Length

Jiangsu, China

LIANZHONG

Negotiable

3-15 days

- ±1%
- Decorations
- 6061 T6 aluminium h section, 0.3mm aluminium h section, 6061 Galvanized H Channel



**Our Product Introduction** 

### ASTM 6061 Silver Aluminium H Beam 0.3mm Thickness Used For Decorations

H-beam steel is an economical and efficient profile with more optimized section area distribution and more reasonable strength-to-weight ratio, so it is named because its section is the same as the English letter "H". Because all parts of H beam are arranged at right angles, H beam has been widely used for its advantages of strong bending resistance, simple construction, cost saving and light structural weight in all directions.

Products Des	scription				
Product Name	H Beam Aluminium Extrusion				
Material	Aluminum alloy: 6063-T5, 6061-T6, 6463-T5.				
Diameter	16mm~200mm				
Thickness	0.6mm~150mm				
Length	1m,3m,5.8m,6m,12m or as required.				
Surface Treatment	Clear anodized, black anodized, hard anodized, polished.				
Color	Reference powder coating swatches and custom colors available.				
Deep Processing	Extrusion/Forging, Heat Treatment, Sandblasting, Anodizing, CNC Machining.				
MOQ	500kg				
Production Capacity	The monthly output is 5,000 tons, and the annual output is 60,000 tons.				
Warranty Period	The surface color can be stable for 10 to 20 years in indoor use.				
Package	Plastic bag+carton+pallet.				

Grade	Hardne	Tensile Strength	Yield Strength	Elongation(%)	
	ss	(MPa)	(MPa)	0.25-1.25mm	1.26-3.0mm
1100	0	89.6	34.5	30	6
	H12	110.3	103.4	4	12
	H14	124.1	117.2	3	10
2024	0	186.2	75.8	18	20
	Т3	482.6	344.7	16	18
	T4	468.8	324.1	20	19
3003	0	110.3	41.4	30	33
	H12	131	124.1	9	11
	H14	151.7	144.8	3	7
5052	0	193.1	89.6	20	21
	H32	227.5	193.1	7	10
	H34	262	213.7	6	8
5083	0	275.8	144.8	21	25
	H32	282.7	151.7	20	21
	H34	330.9	255.1	11	14
6061	0	124.1	55.2	25	26
	T4	241.3	144.8	22	24
	T6	310.3	275.8	12	17
7075	0	227.5	103.4	16	18
	T6	572.3	503.3	11	12

### **Product Details**



Packing and Shippment



Certification



JIANGSU LIANZHONG METAL PRODUCTS (GROUP) CO., LTD

sales02@jslzsteel.com @ aluminium-sheetcoil.com

Guang Yi Columbus B Tower, Wuxi, Jiangsu, China

**(**+8618151700330