

1060 Aluminium H Beam Anti Oxidant H Section Aluminium Channel 0.5mm Thick

Basic Information

- Place of Origin:
- Brand Name:
- Certification: ISO9001
- Model Number:
- Minimum Order Quantity: 1ton
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T, Western Union
- Supply Ability:



Product Specification

- Wall Thickness:
- Temper:
- Delivery Time:
- Length:
- Surface Finish:
- Application:
- Highlight:
- 0.4-100mm Or Accept The Customization T3-T8 Within 7 Days

1000series, 2000series, 3000series,

5000series, 6000series, 7000series

20000 Ton/Tons per Month

Exporting package/wooden box package etc

Custom Length

Jiangsu, China

LIANZHONG

Negotiable

3-15 days

- Anti-oxidant
- Industry
- Aluminium H Beam Anti Oxidant, 1060 Aluminium H Beam, h section aluminium channel 0.5mm



Our Product Introduction

ASTM 1060 Anti-Oxidant Aluminium H Beam 0.5mm Thickness Used For Industry

H-beam steel is an economical and efficient profile with more optimized section area distribution and more reasonable strength-to-weight ratio, so it is named because its section is the same as the English letter "H". Because all parts of H beam are arranged at right angles, H beam has been widely used for its advantages of strong bending resistance, simple construction, cost saving and light structural weight in all directions.

Product Name	Aluminum H beam				
Alloy	1050,1060,1070				
Temper	T5,T6				
Thickness	0.4mm-500mm				
Size	0.5m to 11.85m , non-standard , custom-made				
Tolerance	+0.1mm				
Shape	Rectangle,Customized				
Standard	EN755-9,GB/T 6892-2015,GB 5237.1-2008,JGJ386-2016				
Process	Drilling,bending,welding,precise cutting,punching,etc				
Туре	Flat framework,Corner framework,Beam framework,etc				
Package	sage Standard pallet with waterproof film, or according to your requirement.				

Grade	Hardne	Tensile Strength	Yield Strength	Elongation(%)	
	ss	(MPa)	(MPa)	0.25-1.25mm	1.26-3.0mm
1100	0	89.6	34.5	30	6
	H12	110.3	103.4	4	12
	H14	124.1	117.2	3	10
2024	0	186.2	75.8	18	20
	Т3	482.6	344.7	16	18
	T4	468.8	324.1	20	19
3003	0	110.3	41.4	30	33
	H12	131	124.1	9	11
	H14	151.7	144.8	3	7
5052	0	193.1	89.6	20	21
	H32	227.5	193.1	7	10
	H34	262	213.7	6	8
5083	0	275.8	144.8	21	25
	H32	282.7	151.7	20	21
	H34	330.9	255.1	11	14
6061	0	124.1	55.2	25	26
	T4	241.3	144.8	22	24
	T6	310.3	275.8	12	17
7075	0	227.5	103.4	16	18
	T6	572.3	503.3	11	12

Product Details



Packing and Shippment



Certification



JIANGSU LIANZHONG METAL PRODUCTS (GROUP) CO., LTD

sales02@jslzsteel.com @ aluminium-sheetcoil.com

Guang Yi Columbus B Tower, Wuxi, Jiangsu, China

(+8618151700330