

7001 7075 T6 6001 6063 T5 Aluminum Pipe Hollow Tube Large Diameter Seamless

Our Product Introduction

Basic Information

- Place of Origin: Jiangsu, China
- Brand Name: CHINALCO
- Certification: ISO9001
- Model Number: 1000series, 2000series, 3000series, 5000series, 6000series, 7000series
- Minimum Order Quantity: 1 ton
- Price: Negotiable
- Packaging Details: Exporting package/wooden box package/Or per customers' requirement
- Delivery Time: 3-15 days
- Payment Terms: L/C, T/T, Western Union
- Supply Ability: 2000 Ton/Tons per Month



Product Specification

- Key Word: Aluminum Pipe
- Temper: O, H12, H14, H16, H18, H22, H24, H26, H28, H32, F, H112, T651, T3, T451, T4, T6, Etc
- Delivery Time: Within 7 Days Or By Quality
- Surface Treatment: Mill Finished
- Surface: Seamless, welded
- Material: 1050, 1060, 1070, 1100, 2A11, 2A12, 2014, 2024, 5052, 5A02, 5A06, 5083, 6060, 6061, 6063, 6082, 6351, 6A02, 7075, 7005, 7A04
- Shape: Square Round Ova
- Usage: Transportation Automobile Electrical Agriculture
- Highlight: Large Diameter Aluminum Pipe, 6001 6063 Aluminum Pipe, 7001 7075 Aluminum Pipe



for more products please visit us on aluminium-sheetcoil.com

Product Description

7001 7075 T6 6001 6063 T5 Aluminum Pipe Hollow Tube Large Diameter Seamless

Product Description

Advantages of aluminum pipe: First, welding technology advantages: suitable for industrial production of thin-wall copper aluminum pipe welding technology, known as a world-class problem, is the key technology of air conditioner connection pipe aluminum copper replacement. Second, the service life advantage: from the inner wall of the aluminum pipe, because the refrigerant does not contain moisture, the inner wall of the copper and aluminum connection pipe will not corrode. The third is energy-saving advantage: the connection pipeline between the indoor unit and the outdoor unit of the air conditioner, the lower the heat transfer efficiency, the more energy saving, or the better the heat insulation effect, the more power saving. Fourth, excellent bending performance, easy to install and move.

Model	Aluminum Tube
Material Grade	1000 series: 1050,1060,1070,1080,1100,1435, etc 2000 series: 2011,2014,2017,2024, etc 3000 series: 3002,3003,3104,3204,3030, etc 5000 series: 5005,5025,5040,5056,5083, etc 6000 series: 6101,6003,6061,6063,6020,6201,6262,6082, etc 7000 series: 7003,7005,7050,7075, etc
Size	Outer Diameter: 3 - 250mm Wall Thickness: 0.3 - 50mm Length: 10mm - 6000mm
Standards	ASTM, ASME,EN, JIS, DIN,GB/T etc
Surface Treatment	Mill finished,Anodized,Powder coating,Sand blast,etc
Surface Colors	Nature, silver, bronze, champagne, black, gloden, etc or as customized
Status	T4 T5 T6 or other special status
Usage	aluminum profile for windows doors decoration construction curtain wall
Quality	China Nation Standard GB/T
Packing	Protective film + plastic film or EPE + kraft paper
Certificate	ISO 9001 2008
MOQ	1 tons. Usual 12 tons for a 20 feet container; 24 tons for a 40 feet container.
Press Machine	500-4000 tons all together 64 press lines
Moulding	1. Using our moulds, no fee; 2. Using customer drawing, opening mould, usually about 5 tons the moulding fee is free; 3. Can be digussed.

Product Detail




Chemical Composition

Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Al
1050	0.25	0.4	0.05	0.05	0.05	—	0.05	0.03	99.5
1070	0.2	0.25	0.04	0.03	0.03	—	0.04	0.03	99.7
1100	0.95 Si + Fe	0.05-0.20	0.05	—	—	—	0.1	—	99

2024	0.5	0.5	3.8-4.9	0.30-0.9	1.2-1.8	0.1	0.25	0.15	Rem.
3003	0.6	0.7	0.05-0.20	1.0-1.5	—	—	0.1	—	Rem.
3004	0.3	0.7	0.25	1.0-1.5	0.8-1.3	—	0.25	—	Rem.
3005	0.6	0.7	0.3	1.0-1.5	0.20-0.6	0.1	0.25	0.1	Rem.
5005	0.3	0.7	0.2	0.2	0.50-1.1	0.1	0.25	—	Rem.
5052	0.25	0.4	0.1	0.1	2.2-2.8	0.15-0.35	0.1	—	Rem.
5252	0.08	0.1	0.1	0.1	2.2-2.8	—	0.05	—	Rem.
6061	0.40-0.8	0.7	0.15-0.40	0.15	0.8-1.2	0.04-0.35	0.25	0.15	Rem.
7075	0.4	0.5	1.2-2.0	0.3	2.1-2.9	0.18-0.28	5.1-6.1	0.2	Rem.


Recommend Products



Aluminum Sheet



Aluminum Roofing Sheet




Aluminum Coil



Aluminum Ingot



Aluminum Bar



Aluminum Square Bar



Aluminum Tube




Aluminum Flat Bar

Application



MACHINERY
MANUFACTURING



RAILWAY
ENGINEERING



THE CHEMICAL
INDUSTRY



WATER
CONSERVANCY PROJECT



BUILDING
DECORATION



Product Paking



The Sample Delivery



Certificate



FAQ

Q: what is the terms of delivery?

A: EXW, FOB, CIF, CFR, DDU

Q: What is the terms of packing?

A: Generally, we pack our goods in bundles or coils with rods or belts, we could also pack the goods as the customers' requirement.

Q: What is your delivery time?

A: For stocks, we could transport the goods to loading port within 7 days after we received your deposit. For production period, it usually takes about 15 days-30 days after receiving the deposit.



JIANGSU LIANZHONG METAL PRODUCTS (GROUP) CO., LTD

+8618151700330

sales02@jslzsteel.com

aluminium-sheetcoil.com

Guang Yi Columbus B Tower, Wuxi, Jiangsu, China

